



Aviation Meteorological Services

TAF, TTF & METAR/SPECI Reference Card

This reference card contains selected TAF, TTF & METAR/SPECI information to help users gain a better understanding of aerodrome forecasts and reports.

TAF (Aerodrome Forecast) is a statement of meteorological conditions expected for the specified period of time in the airspace within 5 nautical miles of the aerodrome reference point.

METAR (Meteorological Aerodrome Report) is a routine aerodrome weather report issued at half hourly time intervals.

SPECI (Special Meteorological Report) is a special aerodrome weather report issued only when meteorological parameters meet specific criteria.

TTF (Trend Forecast) is a three hour trend forecast appended to some METAR/SPECI. It supersedes the TAF for its period of validity.

Sample TAF & TTF METAR

TAF AMD YPPH 020328Z 0203/0306
01010KT 9999 -SHRA SCT030
FM020400 25014KT 9999 -SHRA SCT030
FM030300 28020G30KT 9999 -SHRA SCT025
INTER 0203/0208 25015G25KT 4000 SHRA SCT015
INTER 0208/0212 25015G25KT 6000 SHRA SCT020
INTER 0304/0306 28025G35KT 4000 SHRA BKN015
RMK
T 11 15 15 13 Q 1019 1017 1018 1019

TTF SPECI YPPH 020500Z 27007KT 9999 FEW016
SCT035 13/11 Q1018
RMK RF00.4/006.2 HAZE.
INTER 0500/0800 25015G25KT 4000 SHRA SCT015

Elements of TAF, TTF and METAR/SPECI

AUTO will be included when a METAR/SPECI contains only automated observations.

Wind is given in the format DDDSSKT where DDD is the mean direction in degrees True rounded to the nearest 10 degrees and SS is the mean speed in knots (KT).

The maximum gust will be given after the letter G if it is forecast or observed to exceed the mean by 10 knots or more, e.g. 33028G40KT gives a mean wind direction of 330 degrees True, with a mean speed of 28 knots and a maximum gust of 40 knots.

At selected aerodromes, an additional wind variation group may also be included in METAR/SPECI when the wind direction varies by sixty degrees or more during the sampling period used for the wind report. For example, 150V220 indicates that the wind has varied between 150 and 220.

Visibility is given in metres, in a four-figure group (e.g. 0500 = 500m, 2000 = 2000m) with 9999 being used to indicate visibility of 10 kilometres or more.

In METAR/SPECI, two groups may be reported when visibility is not the same in different directions; the prevailing visibility first, then the minimum visibility and its direction (using one of the

eight points of the compass) from the observing station, e.g. 8000 2000NE.

Air temperature (and dewpoint temperature in METAR/SPECI) are given in degrees Celsius in a two-digit group, rounded to the nearest whole degree. Negative values are preceded by M (minus), e.g. M03. In TAF, air temperature values are preceded by the letter T. In METAR/SPECI, the air temperature and dewpoint temperatures are given in the format TT/T_dT_d, where T is the air temperature and T_d is the dewpoint temperature, e.g. 22/15.

QNH is given in hectopascals in a four figure group, e.g. 1008, or 0998. QNH values are preceded by the letter Q. QNH values in METAR/SPECI are rounded down to the whole hectopascal.

TAF issue time and **METAR/SPECI report time** is given in the format DDHHMMZ. For example, 171655Z indicates an issue time of 1655 UTC on the 17th day of the month.

A TAF is normally issued half an hour to two hours prior to the start of the validity period.

Validity period for a TAF is given in the format DDHH/DDHH, e.g. 1718/1824 indicates a validity of thirty hours from 1800 UTC on the 17th.

Did You Know?

In TAF, the four temperature and QNH values are point forecasts for HH, HH+3, HH+6 and HH+9 where HH is the commencement of the TAF validity.

Users should use a linear interpolation to determine the forecast value between these points.

Cloud Information

Code	Cloud Amount
FEW	Few (1 to 2 oktas)
SCT	Scattered (3 to 4 oktas)
BKN	Broken (5 to 7 oktas)
OVC	Overcast (8 oktas)
NSC	Nil Significant cloud
NCD	Nil cloud detected (in AUTO reports only)

Cloud amount is forecast or reported using the abbreviations above.

Cloud information in TAF and METAR/SPECI is given in the order of lowest to highest in accordance with the following rules:

1st group is the lowest layer regardless of amount. **2nd group** is the next layer covering more than two eighths of sky. **3rd group** is the next layer covering more than 4 eighths of sky.

Extra groups - cumulonimbus (CB) and towering cumulus (TCU) when not included in the above.

Cloud type is not given except for CB and TCU.

Weather Information

Prefix	Weather Intensity
+	Heavy
no prefix	Moderate
-	Light
Code	Weather Descriptor
BC	Patches
BL	Blowing
DR	Drifting
FZ	Freezing
MI	Shallow
PR	Partial
SH	Showers
TS	Thunderstorm
VC	in the Vicinity
Code	Weather Phenomenon
BR	Mist
DU	Dust
DS	Duststorm
DZ	Drizzle
FC	Funnel cloud
FG	Fog
FU	Smoke
GR	Hail
GS	Small hail/snow pellets
HZ	Haze
PL	Ice pellets
PO	Dust devil
RA	Rain
SA	Sand
SG	Snow grains
SN	Snow
SQ	Squall
SS	Sandstorm
VA	Volcanic ash
UP	Unidentified precipitation

Weather is included in a forecast or report using the abbreviations in the table (left). Examples are:

BCFG for fog patches.

SHRA for moderate showers of rain.

Intensity is indicated for precipitation, dust storms, sandstorms and funnel clouds (tornados and water spouts), by prefixing the weather groups as shown in these examples:

+TSRA for thunderstorm with heavy rain showers.

DZ for moderate drizzle.

-RA for light rain.

Common Abbreviations

BECMG Becoming

CAVOK Cloud and visibility and weather ok

FM From

INTER Intermittent variations – periods < 30 mins in a hour

MOD Moderate

PROB30 30% chance of forecast conditions occurring

PROB40 40% chance of forecast conditions occurring

RMK (remark) in TAF precedes information on temperatures and QNH, and turbulence if forecast

SEV Severe

TEMPO Temporary variations – periods of 30 mins to < 60 mins

Z Appended at the end of issue and validity times to signify UTC (Coordinated Universal Time)

More abbreviations can be found in the AIP Book

