

# Metadata for Tidal Data Exchange

**Station Name**      **Burnie**

Date of Supply      Tuesday, 12 August 2025

Identification		
Station Number	BoM=091344 ANTT=60910	
Name	Burnie	
Latitude and Estimated Positional Uncertainty	-41.05	+/- 3m
Longitude and Estimated Positional Uncertainty	145.9149	+/- 3m
Map Name	Hellyer	
Map Number	8015	
Map Grid Northing	N/A	
Map Grid Easting	N/A	
Type of Readings		
Heights	Observations	
Progress *	See comments section.	
Update Frequency *	Real Time	
Available Format Type *	DIGITAL, text	
Measurement Units		
Tidal Heights	metres	
Reference Frame		
Time Zone	UTC	
Vertical Reference Frame	Tide Gauge Zero (m)	
TGBM Name/Number	SPM 9087 Brass Lands disc in concrete mooring block	
TGBM Elevation relative to the vertical reference	3.062 m AHD or 5.000 m TGZ (2006)	
Estimated Positional Uncertainty	+/- 2mm	
Horizontal Reference Frame Direction of Stream Readings Depth of Stream Readings (relative to Vertical Reference Frame) Estimated Positional Uncertainty	Geodetic Datum of Aust (GDA94)	
Search Words *	Marine, Oceanography, Water, Burnie	
Data Owner Details		
Name	Bureau of Meteorology	
Postal Address	GPO Box 1289, Melbourne VIC 3001	
Street Address	700 Collins Street, Docklands, VIC 3008	
Telephone		
Facsimile		
Email	tides@bom.gov.au	
Internet	www.bom.gov.au	
Contact Officer Details		
Name	Marine and Antarctic, Environmental Prediction Services	
Position	Tidal Services	
Telephone		
Email	tides@bom.gov.au	
Data Custodian Details		
Name	Bureau of Meteorology	
Postal Address	GPO Box 1289, Melbourne VIC 3001	
Street Address	700 Collins Street, Docklands, VIC 3008	
Telephone		
Facsimile		
Email	tides@bom.gov.au	

# Metadata for Tidal Data Exchange

**Station Name**                      **Burnie**

Date of Supply                      Tuesday, 12 August 2025

Internet	www.bom.gov.au
Contact Officer Details	
Name	Marine and Antarctic, Environmental Prediction Services
Position	Tidal Services
Telephone	
Email	tides@bom.gov.au
<b>Details of the Readings Provided Herewith</b>	
Date of readings supplied	
From	9/4/1992
To	Current
The time interval between readings (If the readings are for high & low water then enter "Zero")	1-minute (average of 60, 1-second samples) 6-minutes (weighted average of 4, 1-minute readings) Hourly (filtered with a cut-off of 2 hours)
Are the readings averaged or filtered	See above. 1-minute samples are logged at the end of each minute, 6-minute centred on 0.1-hour increments
Are there any access constraints (such as commercial-in-confidence or constraint on the use or distribution to third parties).	No
<b>Objective Quality Assessment of Tidal Observations (Height or Stream)</b>	
<b>Instrument</b>	
Type Model	Digital data logger Sutron 9000 (1992-2009)/Telmet 320 RTU (2009-current)
<b>Sensor</b>	
Type Model	Acoustic-in-air sensor Aquatrak® Transducer
<b>Frequency of System Calibrations</b>	
Field calibration and Laboratory calibration	every 1-2 years every 1-2 years
<b>Frequency of Water Level Checks</b>	Daily
<b>Estimate of the Precision of the Water Level Checks</b>	
Time (Std Dev in Minutes) Height (Std Dev in metres)	GPS Satellite Clock 1mm +/-
<b>System Resolution</b>	1mm +/-
<b>Estimated Local Uncertainty</b>	
<b>Status of the Readings</b>	Statistical analysis
<b>Description of the validation process including a statement detailing how:</b>	
1. The instrumental biases were treated	Standard deviations
2. Outliers were selected and dealt with	Reported
3. Breaks in the record were dealt with	Recovered where possible
<b>Date of Validation</b>	Checked each month, for previous month
<b>Name of Person certifying the validation</b>	Tidal Services
<b>Details required with the supply of tidal constituent constants</b>	
All of the details required above	
The name and version of the software used to calculate the constants	Tans

## Metadata for Tidal Data Exchange

**Station Name**                **Burnie**

**Date of Supply**                Tuesday, 12 August 2025

The tidal constituent model used (particularly noting the treatment of the constituents Sa and Ssa) and specifying any related (inferred) constituent constants	Doodson's method
The date span used to prepare the constituent constants	1992-2023 (for 2026)
The reference time zone for the constituents	AEST (-1000)
The vertical datum to which the constituents apply	LAT, which is 0.02m below TGZ and 1.958m below AHD
A precision estimate of predictions based on the constituent constants (for example, standard deviation of the analysis residuals)	Standard Deviation is 0.1138
<b>Additional details required with the supply of tidal predictions</b>	
All of the details required above	
A statement describing the tidal prediction process used	Doodson's method
The name and version of the software used to calculate the predictions	Tipp5
A list of the constituent constants used or if the list is not provided, the donor agency's identifier of the list	Standard 112 Constituent list

### Comments on data by Port Authority

- Australian Baseline Sea Level Monitoring Array (ABSLMA)
- Before 24-Jul-2009, Sutron Logger used. 6-minute samples average of 181, 1-second samples
- Earlier data read from analog tide gauge traces on the hour